

Wood.Protector

LIQUID
SOLUTIONS

Wood.Protector

It is not just necessary to produce quality – it is also important to preserve it!

The wood preservation agent **Wood.Protector** was specially developed to completely prevent hardwoods from cracking (dry cracks) without causing disadvantages for the wood or kiln drying.



Excellent results have also been accomplished in steaming because **Wood.Protector** resists very high temperatures. Applications are for all kinds of cut to size material as well as the protection of lumber and logs.

Wood.Protector:

- Economical consumption
- Suitable for spraying and painting
- Does not cause lubrication or slipping
- Remains stable at high temperatures
- Does not soak into the wood
- No negative effects on tools and machines
- Water-dilutable
- Easy to remove in fresh state
- Processing temperature: from 0°C
- High durability
- Non-combustable in fresh state
- Non-toxic



Without Wood.Protector



With Wood.Protector

Packages:

Wood.Protector

Pallets with 24 buckets á 25 kg (600 kg)
IBC (1.400 kg)
Wood.Protector 1L = 1,5 kg

Colour:

From an order quantity of 1.200 kg, we can fulfill any company-specific color request at no extra charge.

Contact:

Liquid Solutions

+43 (0) 650 6621766
office@liquidsolutions.at
www.liquidsolutions.at